Product Information Sheet

dimensions

Width

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources		, , , , ,	_		
Supplier's name	e or trade mark:	V-TAC			
Supplier's addre	ess: V-TAC Europ	e Ltd, bul. Rozhen 4	1, Sofia, Bulgaria		
Model identifie	r: 212041				
Type of light so	urce:				
Lighting technology used:		LED	Non-directional or directional:	NDLS	
Light source cap-type		+ve and -ve			
(or other electric interface)					
Mains or non-mains:		NMLS	Connected light source (CLS):	No	
Colour-tuneable light source:		No	Envelope:	-	
High luminance light source:		No			
Anti-glare shield:		No	Dimmable:	Only with specific dimmers	
Product parameters					
Parameter		Value	Parameter	Value	
		General product p	parameters:		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		5	Energy efficiency class	F	
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		420 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000	
On-mode power (P _{on}), expressed in W		4,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80	
Outer	Height	4	Spectral power	See image	

distribution in the

in last page

500	range 250 nm to 800 nm, at full-load				
-	If yes, equivalent power (W)	-			
	Chromaticity	0,379			
	coordinates (x and y)	0,379			
Parameters for LED and OLED light sources:					
11	Survival factor	1,00			
0,96					
	ght sources:	nm, at full-load If yes, equivalent power (W) Chromaticity coordinates (x and y) ght sources: 11 Survival factor			

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

